

403A-15G2

APS -P16

Series

Generator made by OEM-Perkins

- Every generating set carries a comprehensive test program & report thereon.
- Certifications: ISO 8528/1, ISO 3046/1:1986, BS5514/1, NEMA MG1-22, NEMA MG 1.32-33, IEC 60034, BS 5000 PART 99, VDE 0530, ISO 8528/3, UL 1446, UL 1004, ISO 9001, ISO 14001, AS 1359, IEC34.
- Complete protection functions & safety labels.
- Easy & Economical availability of Spares.
- Advanced digital control system, long service life, easy to operate, low fuel consumption & anti-vibrating isolators.
- After Sales support all over Pakistan.
- High quality, reliable & complete generating set.
- Easy for operation & maintenance.

GENERATOR SET

- Model: APS-P16
- Prime Power: 15-KW 12-KVA
- Standby Power: 16.5-KVA 13.2-KW
- Configuration: 380-415 V, 3Ph, 50 Hz, 1500 RPM at 0.8 PF

FUEL CONSUMPTION


- Consumption @ 100% load: 4.3 Ltrs
- Consumption @ 75% load: 3.1 Ltrs
- Consumption @ 50% load: 2.2 Ltrs

DIMENSIONS, WEIGHT & FUEL TANK (Approx.)

Particulars	Open	Canopy-R	Canopy-S
Length (Inches)	54	57	71
Width (Inches)	23	34	36
Height (Inches)	45	48	38
Net Weight (Kg)	472	612	623
Fuel Tank (L)	-	85	78

Ratings & Standard Reference Conditions

- Prime Power: Continuous power at variable load, replacing utility power, with 10% overload available for 1 hour every 12 hours.
- Standby Power: Continuous electrical power at variable load during utility power failure. No overload permitted.
- Air Inlet Temperature: at 25°C
- Altitude Capability: De-rating may apply depending on site conditions
- Notes: Some specifications may not be standard on all genset models



ALTERNATOR DATA:

Manufacturer	LEROY SOMER	STAMFORD	Equivalent
Model /Series	TAL Series	TBA	TBA
Frequency /Speed	50 Hz	1500 RPM	
Coupling	Direct	-	
Over speed	2250 mn-1	-	
No. of Bearings	Single Bearing		
AVR Model	R120		
Phase / Poles	± 1%		
Voltage Regulation	3-Phase		
Ingress Protection	IP 23		
Winding Pitch	H		
Insulation Class	Shunt		
Excitation	2/3 (wdg 3)		



ENGINE SPECIFICATIONS

ENGINE DATA

- Manufacturer: Perkins
- Model: 403A-15G2
- Fuel Type: Diesel
- Recommended Fuel Grade: #2

Engine Configuration

- Number of Cylinders: 3
- Cylinder Arrangement: Vertical In-Line
- Displacement: 1.4961 L
- Cycle: 4-Stroke
- Aspiration System: Naturally Aspirated
- Combustion System: Direct Injection
- Governor Type: Mechanical
- Rotation: Anti-Clockwise
- Compression Ratio: 22:5:1

Dimensions & Performance

- Bore: 84 mm
- Stroke: 90 mm
- Rated Speed: 1500 RPM @ 50 Hz

Power Output

- Gross Power PRP: 14-KWm /18-HP
- Gross Power STP: 15.4-KWm /20.1-HP

Electrical System

- Battery Voltage: 12 V
- Battery Charging Alternator: 15 Amps
- Starter Motor: 2 kW, 12 V

OTHER INFORMATION:

- ATS /AMF Panel : Optional
- External Fuel Tank : Optional
- Trailer/Trolley : Optional
- Remote Monitoring : Optional
- Operating Temperature : Up to 50° C
- Low Fuel Level Sensor : Available
- 4-Pole Breaker : Optional
- Sound Level @ 7M : 74 dBs (Approx.)
- Synchronizing System : Optional
- Customized Color : Optional

Air & Exhaust System

- Combustion Air Flow: 1 m³/min
- Exhaust Gas Flow: 2.2 m³/min
- Exhaust Gas Temperature: 470°C
- Allowable Back Pressure: 10 kPa
- Exhaust Outlet Size: 42 mm

Lubrication System

- Lubricating Oil Capacity: 6 L
- Oil Pressure: 262-359 kPa
- Recommended Oil Grade: API CH-4, SAE 15W-40

Cooling System

- Cooling Type: Water Cooled
- Coolant Capacity: 6 L
- Coolant & Water Ratio: 50 : 50
- Radiator Cooling Air Flow: 0.42 m³/s (Minimum)
- Thermostat Operating Range: 82 – 95 °C

Standard Specifications

Component	Details
Engine	Perkins 4-stroke diesel engine
Filtration System	Air, fuel & lube oil filters
Cooling & Exhaust	Radiator with fan & guard
Circuit Breaker	3-pole MCB (4-pole optional)
Fuel System	Integral fuel tank, 5–8 hrs
Alternator	Class H insulated windings
Voltage Regulation	Automatic AVR, ±0.5% regulation
Mounting Arrangement	Frame with anti-vibration support
Factory Tests	Load-tested, protections verified
Documentation	O&M manual, wiring diagrams
Warranty	12 months / 1000 hrs warranty

Controller Data	
Make	Deep Sea-UK
Model	DSE 4520



ADVANCED POWER SOLUTIONS
Office #205, Asad Business Centre, Model Town, Lahore
Tel: +92 300 811 2242
Fax: +92 300 844 0485
www.aps.com.pk



Perkins®
THE HEART OF EVERY GREAT MACHINE
Perkins Engines Company Limited
Peterborough, PE15FQ, United Kingdom

CONTROLLER & PROTECTIVE FUNCTIONS

Controller LCD Display

Component	Deep Sea DSE 4520	Deep Sea DSE 6020
Voltage between Phases (L-L)	✓	✓
Voltage between Neutral and Phase (L-N)	✓	✓
Frequency and 3 Phase Current	✓	✓
Real Power (KW) and Apparent Power (KVA)	✓	✓
Power Factor	✓	✓
Engine Speed	✓	✓
Running Hours	✓	✓
Coolant Temperature	✓	✓
Oil Pressure	✓	✓
Battery Voltage	✓	✓
LCD Alarm Indication	✓	✓
3 Phase Mains (Utility) Sensing	✓	✓

Protecting Functions

Component	Deep Sea DSE 4520	Deep Sea DSE 6020
Emergency Stop Button	✓	✓
High coolant Temperature	✓	✓
Low Oil Pressure	✓	✓
Over Current / Load	✓	✓
Under/Over Speed, Frequency	✓	✓
Mounting Arrangement	✓	✓
Low / High Battery Voltages	✓	✓
Low Fuel Level Warning at 20%	✓	✓

